

Item	Qty	Description of products and services	Price per unit	Amount
------	-----	--------------------------------------	----------------	--------

		<p><b>Blower Actuator, 2-fold, 6 A, MDRC</b></p> <p>The Blower Actuator independently switches two 1- to 3-speed fans, controlled via KNX, by means of floating contacts.</p> <ul style="list-style-type: none"> <li>- Switching of two multi-level resistive, inductive or capacitive loads</li> <li>- Contacts per fan connection with common foot point</li> <li>- Second fan connection alternatively as 3 switching outputs</li> <li>- Two additional floating switching outputs</li> </ul> <ul style="list-style-type: none"> <li>- Speed switching or changeover switching can be parameterized</li> <li>- Direct selection of fan speed</li> <li>- Increase and decrease fan speed</li> <li>- Control fan speed via up to 2 control values</li> <li>- Control value selection by switchover or maximum selection</li> <li>- Threshold value with hysteresis for fan speeds</li> <li>- Forced operation</li> <li>- Limitation</li> <li>- Selection of fan speed on bus voltage failure</li> <li>- Selection of fan speed on bus voltage recovery</li> <li>- Start-up behavior can be parameterized</li> <li>- Switchover pause between fan speeds can be parameterized</li> <li>- Fan run-on can be individually parameterized for every speed</li> <li>- Control value monitoring can be parameterized</li> <li>- Switching outputs can be parameterized as n/o contacts or n/c contacts</li> <li>- Switching outputs with staircase lighting function</li> <li>- Status feedback</li> <li>- Reaction of outputs on bus voltage failure can be parameterized</li> <li>- Reaction of outputs on bus voltage recovery can be parameterized</li> <li>- Sending delay after bus voltage recovery</li> <li>- "In Operation" object (cyclic alive signal)</li> </ul> <p>Outputs: 8 (2x 3 + 2x 1)  Rated current per output: 6 AX (250 / 440 V AC)  Max. power consumption of device: 2 W  Switching capacity</p> <ul style="list-style-type: none"> <li>- To DIN EN 60 947-4-1: 6 A / AC3</li> <li>- To DIN EN 60 669: 6 AX</li> <li>- Max. capacitive load: 140 µF</li> <li>- Max. peak inrush current (150 µs): 400 A</li> </ul> <p>Connection: Screw terminals with universal head screw  Load circuit: For 0.2 to 6 mm<sup>2</sup> cables  KNX: Screwless bus connection terminal  Degree of protection: IP 20, EN 60 529  Mounting: On 35 mm mounting rail, DIN EN 60 715  Mounting position: Any  Width: 6 space units (108 mm)</p> <p>Delivery, mounting incl. accessories: .....  Start-up: .....</p> <p>Manufacturer: ABB STOTZ-KONTAKT  <b>Make like:</b> <b>FCL/S 2.6.1.1</b>  or equivalent</p> <p>Quantity: .....</p>	Carry:	
--	--	--	--------	--

		FCLS_2611_AT_EN_V2-0 2CDC 508 133 D0201	Carry:	
--	--	--	--------	--