

MDT DaliControl Gateway, MDRC

Version		
SCN-DALI16.03	DaliControl IP Gateway	4SU MDRC, up to 64 ECG in 16 channels/light groups

The MDT DaliControl Gateway is the interface between DALI lights and the KNX installation and offers many new possibilities, such as the light control in the HSV color space.

Up to 64 DALI ECGs can be assigned to any 16 channels / light groups. For each group the functions switching, dimming and brightness value are available. The DaliControl Gateway supports various color control modes (according to DALI DT8 standard) such as HSV color space, RGB / RGBW, XY color and the color control mode Tunable White. With the integrated color control module 16 individual time-dependent lighting moods with up to 300 control commands can be created. The scene control allows to assign all 16 groups to the 16 possible scenes as desired with individual dimming times.

The MDT DaliControl Gateway provides the operating modes normal operation, continuous operation, night operation, staircase operation and panic operation. The individual light groups can be switched between 1-8 and 9-16 using the buttons for manual operation. Faulty ECGs can be detected individually or at group level. In the event of a fault, a simple quick exchange of the affected ECG is possible.

The free DCA app is used for the commissioning of the DALI bus system, the configuration of the scenes and the time-dependent lighting moods.

The MDT DaliControl Gateway is a modular installation device for fixed installation in dry rooms. It fits on 35mm rails in power distribution boards or closed compact boxes.

For project design and commissioning of the MDT DaliControl Gateway it is recommended to use the ETS. Please download the application software at www.mdt.de/Downloads.html

SCN-DALI16.03



- Production in Germany certified according to ISO 9001
- Supports different DALI ECG
- **Control of up to 16 channels / light groups** (switching, dimming, and brightness value)
- **Innovative HSV color control, RGB, RGBW and XY color according to Dali DT8 standard**
- **Tunable White, color temperature control**
- **Integrated color control module for at time dependent controlling of the luminous color** in up to 300 steps
- Operation modes like normal operation, continuous operation, night operation, stairwell operation and panic operation
- Manual operation for all 16 groups
- 16 scenes with individual dimming times
- **Energy saving function for switching off the ECGs** (via additional KNX switch actuator)
- Fault detection of lamp faults and faulty ECGs
- Quick exchange of ECG
- **Free DCA app for commissioning** the DALI bus system and configuration of the scenes and time control
- 3 years warranty

Technical Data	SCN-DALI16.03
Outputs	
Number of groups	16
Number of ECG	64
Maximum Dali voltage	16-20VDC
Maximum Dali current	250mA
Permitted wire gauge	
Screw terminal	0,5 - 4,0mm ² solid core 0,5 - 2,5mm ² finely stranded
KNX busconnection terminal	0,8mm Ø, solid core
Power Supply	230VAC/50Hz
Power consumption mains 230VAC typ.	< 5W
Operation temperature range	0 bis + 45°C
Enclosure	IP 20
Dimensions MDRC (Space Units)	4SU

Exemplary circuit diagram SCN-DALI16.03

