

Photo-cell controller

Light Sensor Dual

V3 KNX - surface, rd.
EAN 4007841 058333

STEINEL[®]
PROFESSIONAL



Twilight switch +
eco-mode



KNX



IP54



2 - 1000 lux



max 4 m



CE



5 JAHRE
HERSTELLER
GARANTIE
steinel-professional.de/garantie

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

Type	Constant-lighting controller	Basic light level function	Yes
Dimensions (Ø x H)	126 x 56 mm	KNX functions	Light output 2x, Light level, Constant-lighting control, Photo-cell controller
Sensor Technology	Light sensor	With bus coupling	Yes
Application, place	Outdoors, Indoors	Settings via	ETS software, Remote control, Bus, Smart Remote
Application, place, room	classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room, Indoors	IP-rating	IP54
Installation site	wall, ceiling	Version	KNX - surface, rd.
Installation	Surface wiring	PU1, EAN	4007841058333
Mounting height	2,00 – 4,00 m		

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Photo-cell controller

Light Sensor Dual

V3 KNX - surface, rd.

EAN 4007841 058333

STEINEL[®]
PROFESSIONAL

Dimension Drawing

