

Item	Qty	Description of products and services	Price per unit	Amount
------	-----	--------------------------------------	----------------	--------

		<p><b>Busbar, 1-phase, 4 contacts, 6 mm<sup>2</sup></b></p> <p>The busbar enable fast and fault-free wiring of the load side of the ABB i-bus<sup>®</sup> modular installation devices and accordingly reduce the wiring effort.</p> <p>The busbar is a device for the interconnection of ABB i-bus<sup>®</sup> devices with 6 mm<sup>2</sup> terminals (e.g. SA/S 10/16/20A, SD/S, LR/S 4.16.1 etc.).</p> <p>It is suited for wiring in distribution boards as well as in control panels.</p> <p>The prefabricated busbar can be used for supplying power for up to 4 load circuits.</p> <p>The busbar has an end cup PS-END 1-S, which prevents touching or contact with live parts and components.</p> <p>Rated current                      40 A</p> <p>Rated voltage                      250/440 V</p> <p>Cu cross-section                      6 mm<sup>2</sup></p> <p>Length                              62 mm (4 contact pins)</p> <p>Manufacturer                      ABB STOTZ-KONTAKT</p> <p><b>Type                              PS 1/4/6-KNX</b></p> <p>Material: .....                      Labour: .....</p>	Carry:	
--	--	--	--------	--

		PS_146_KNX_AT_EN_V2-0 2CDC 503 031 D0201	Carry:	
--	--	---	--------	--

PS 1/4/6-KNX

PS 1/4/6-KNX