



Card holder, universal Square 86 x 86 mm Configurable device

Functions at a glance

- Ordering possible only in connection with the design ID.
- For inserting mifare RF cards.
- The icons and/or texts are configured by means of a web configuration tool.
- Freely programmable function "Do not disturb", "Bell" and "Make up room".
- Number of bus subscribers: 1 with separate 24 V auxiliary power supply
- Display elements: Two LED per rocker via separate communication object for status (Red/ Green/ OFF) or orientation light.
- Rated voltage: 12 V/24 V
- Outputs: 1
- Laststart: AC/DC
- Rated current: 4 A
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -20 °C - 70 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 86 mm x 86 mm
- These tailor-made devices are excluded from being exchanged.
- Figure shows the configured device.
- Ordering possible only in connection with the specified design ID or the design ID received via the configurator.
- For software and description please check the current Online-Catalogue.
- Mounting is done in common standard flush-mounted device boxes, e.g. according to DIN49073, part 1
- Delivery time approx 10 working days after order.
- Article is also available as standard device with standard ICON with Design ID F5XVP551 (white glass 811) or ID F5XVP55M (black glass 825).

Order details

Article No.:	TKK/U.1.11-CG
Order No.:	2CKA006300A1572
EAN:	4011395231098
Preisgruppe:	42
Preis:	264,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Certificates

» [ROHS product declaration](#)