



# Room outdoor sensor

## Square 86 x 86 mm

### Configurable device

#### Functions at a glance

- Ordering possible only in connection with the design ID.
- The icons and/or texts are configured by means of a web configuration tool.
- Freely programmable function "Do not disturb", "Bell" and "Make up room".
- Push switch function: switching / dimming / blind / sending values / scenes etc.
- Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green.
- With integrated KNX bus coupler.
- With integrated temperature sensor.
- With integrated proximity function.
- The bus connection is provided via the enclosed bus terminal.
- Number of bus subscribers: 1
- Control element: freely programmable touch surfaces
- Display elements: Two LED per rocker via separate communication object for status (Red/ Green/ OFF) or orientation light.
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -20 °C - 70 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 86 mm x 86 mm
- These tailor-made devices are excluded from being exchanged.
- Figure shows the configured device.
- Ordering possible only in connection with the specified design ID or the design ID received via the configurator.
- For software and description please check the current Online-Catalogue.
- Mounting is done in common standard flush-mounted device boxes, e.g. according to DIN49073, part 1
- Delivery time approx 10 working days after order.

#### Order details

<b>Article No.:</b>	TA/U3.1.11-CG
<b>Order No.:</b>	2CKA006300A1569
<b>EAN:</b>	4011395231067
<b>Preisgruppe:</b>	42
<b>Preis:</b>	205,00 EUR plus VAT
<b>Info sheet:</b>	» <a href="#">Download PDF</a>

#### Downloads

##### Instruction manual

- » [Installation and operating instructions](#)
- » [Product manual](#)

##### Certificates

- » [EU-declaration of conformity](#)

##### Software

- » [ETS4/ETS5 application , V 2.0, 06.08.2019](#)
- » [Firmware , V 1.1, 15.10.2018](#)