



Busch-Watchdog 180 flush-mounted standard sensor Square 86 x 86 mm Configurable device

Functions at a glance

- Ordering possible only in connection with the design ID.
- Movement detector with up to 4 channels.
- The bus can be connected via enclosed terminal block.
- With integrated temperature sensor.
- With integrated KNX bus coupler.
- Number of bus subscribers: 1
- Control element: Setting via ETS application.
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -20 °C - 70 °C
- Transport temperature range: -25 °C - 70 °C
- Detection range: frontal: 6 m, lateral: 6 m
- Brightness limit value: 1 Lux
- Detection angle: 180 °
- Dimensions: (L x W x D): 86 mm x 86 mm x 30 mm
- Position for installation: vertical
- Mounting height: 1.1 m - 1.3 m
- These tailor-made devices are excluded from being exchanged.
- Figure shows the configured device.
- Ordering possible only in connection with the specified design ID or the design ID received via the configurator.
- For software and description please check the current Online-Catalogue.
- Mounting is done in common standard flush-mounted device boxes, e.g. according to DIN49073, part 1
- Delivery time approx 10 working days after order.

Order details

Article No.:	TBW/U.1.11-CG
Order No.:	2CKA006300A1568
EAN:	4011395231050
Preisgruppe:	42
Preis:	172,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

- » [Installation and operating instructions](#)
- » [Product manual](#)

Certificates

- » [EU-declaration of conformity](#)

Software

- » [ETS4/ETS5 application , V 2.0, 06.08.2019](#)