



Analogue input 4gang

Functions at a glance

- The analogue input enables the detection and processing of four analogue input signals.
- These are, among others: 0-1 V, 0-5 V, 0-10 V, 1-10 V, 0-20 mA, 4-20 mA, 0-1000 ohm, Pt100, floating contact, KT, KTY, and user-defined.
- A power pack with 24 V DC voltage has been integrated to supply the sensors.
- Rated voltage: 230 V~, +10 % / -10 %
- Rated frequency: 50 Hz / 60 Hz
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 90 mm x 72 mm x 64 mm
- Module width: 4
- Mounting depth: 68 mm

Order details

Article No.:	6190/51-101
Order No.:	2CKA006190A0046
EAN:	4011395193594
Preisgruppe:	44
Preis:	256,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

» [DE, EN, ES, FR, NL, PL, RU](#)

Technical manual

» [DE](#)

Certificates

» [EU-declaration of conformity](#)
 » [ROHS product declaration](#)

Software

» [ETS3 application , V 1.2, 24.05.2017](#)
 » [Additional software :i-bus tool , V 1.9.37.0, 25.02.2019](#)