



## Blind actuator, 6 A with "in-situ operation" 4gang

### Functions at a glance

- 230 V~, 50 Hz, 4 x 6 A
- For controlling of 4 independent blind groups.
- Rated voltage: 230 V~, +10 % / -15 %
- Rated frequency: 50 Hz / 60 Hz
- Outputs: 4 Change-over switch
- Lastart: AC1/AC3
- Rated current: 6 A
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 90 mm x 72 mm x 64 mm
- Module width: 4
- Mounting depth: 68 mm
- ETS programming only from ETS 3f.
- Also usable as a binary output (one channel per output).

### Order details

<b>Article No.:</b>	6196/42-102
<b>Order No.:</b>	2CKA006151A0220
<b>EAN:</b>	4011395132425
<b>Preisgruppe:</b>	44
<b>Preis:</b>	306,00 EUR plus VAT
<b>Info sheet:</b>	» <a href="#">Download PDF</a>

### Downloads

#### Instruction manual

» [DE](#)

#### Technical manual

» [Technical manual](#)

#### Certificates

» [EU-declaration of conformity](#)

#### Software

- » [ETS4/ETS5 application , V 1.4, 24.07.2017](#)
- » [ETS3 application , V 1.4, 24.07.2017](#)
- » [Additional software :i-bus tool , V 1.9.37.0, 25.02.2019](#)