



Blind actuator, 24 V, 6 A 4gang

Functions at a glance

- 24 V DC, 4 x 6 A
- For controlling of 4 independent blind groups.
- Rated voltage: 24 V
- Outputs: 4 Change-over switch
- Rated current: 6 A
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 90 mm x 72 mm x 64 mm
- Module width: 4
- Mounting depth: 68 mm
- ETS programming only from ETS 3f.
- Also usable as a binary output (one channel per output).

Order details

Article No.:	6196/41-102
Order No.:	2CKA006151A0222
EAN:	4011395132449
Preisgruppe:	44
Preis:	304,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

» [DE](#)

Technical manual

» [Technical manual](#)

Certificates

» [EU-declaration of conformity](#)

Software

- » [ETS4/ETS5 application , V 1.4, 24.07.2017](#)
- » [ETS3 application , V 1.4, 24.07.2017](#)
- » [Additional software :i-bus tool , V 1.9.37.0, 25.02.2019](#)