

Roller blind actuator, 6 A 8gang



Functions at a glance

- 230 V~, 50 Hz, 4 x 6 A
- For controlling 8 independent groups of roller shutters.
- Rated voltage: 230 V~, +10 % / -15 %
- Rated frequency: 50 Hz / 60 Hz
- Outputs: 8 Change-over switch
- Lastart: AC1/AC3
- Rated current: 6 A
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 90 mm x 144 mm x 64 mm
- Module width: 8
- Mounting depth: 68 mm
- The device has a lesser range of functions than the blind actuators.

Order details

Article No.:	6196/83-102
Order No.:	2CKA006151A0224
EAN:	4011395132463
Preisgruppe:	44
Preis:	404,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

» [INT](#)

Technical manual

» [Technical manual](#)

Certificates

» [EU-declaration of conformity](#)

Software

- » [ETS4/ETS5 application , V 1.4, 24.07.2017](#)
- » [ETS3 application , V 1.4, 24.07.2017](#)
- » [Additional software :i-bus tool , V 1.9.37.0, 25.02.2019](#)