


## KNX Water-protected surface-mounted push-button bus coupler, 2-gang with single-point operation



Specification	Order No.	Packing unit	PS	EAN
 grey	5161 30	1	06	4010337500087

The push-button bus coupler is the interface between the KNX system and the user.

### Features

#### Button function

- Switching, dimming, blind, value transmitter 1-byte, and scene auxiliary unit.
- The rocker can only be operated on one side (bottom) during single-point operation (slanted rocker).
- Switching function: Command for pressing and releasing the buttons can be parameterised (ON, OFF, CHANGE, no reaction).
- Push-button bus coupler in the water-protected surface-mounted system (IP 44).
- Dimming function: Command for pressing the buttons can be parameterised (Brighter-ON, Darker-OFF, Brighter or Darker-CHANGE, Brighter-CHANGE, Darker-CHANGE, no reaction).
- Blind function: Command for pressing the buttons can be parameterised (UP, DOWN, no reaction).
- Value transmitter 1-byte function: Mode of operation can be configured.
- Scene auxiliary unit function: Mode of operation can be configured (with or without block function for pressing and holding a button).

### Technical data

KNX connection:	Connection and branch terminal
Protection type:	IP 44
Protection class:	III
Ambient temperature:	-25 °C to +55 °C
Relative humidity:	5 to 93 % (no condensation)

## Scope of supply

- KNX connection and branch terminal included in the scope of supply.

---