

Product data sheet



Room controller display module 2-gang



Reference number

RCD LS 4092 M

can be extended by means of a push-button extension module, ref.-no.: 409.. TSEM

recommended mounting height: 1.5 m

Intended use

- Operation of consumers, e.g. lights on/off, dimming, blinds/shutters up/down, brightness values, temperatures, storing and recalling of light scenes etc.
- Room temperature control
- Fan coil application with up to 4 fan speeds and auto function
- LCD display is freely programmable (14 byte string text) with up to 4 pages with up to 3 lines
- Installation in mounting box according to DIN 49073

Product characteristics

- Push-button functions for switching, dimming, blinds control, valuator, light scenes, etc.
 - Vertical and horizontal key/rocker functions
 - Two red LEDs per control key as status or operation indicators
 - Display of values and texts
 - Running text display for one or two messages with max. 14 characters
 - Integrated room temperature sensor
 - Room temperature control with setpoint value preset
 - Display of room temperature and setpoint temperature
 - Indication of outside temperature (only with external sensor)
 - Integrated bus coupling unit
 - In combination with Facility Pilot "Multi-Room Control": music play control, display of music titles, artists, etc.
 - Display unit for the KNX central alarm unit
 - Transparent cover kit (included) for temporary site use without design covers
-
- Connection for a push-button extension module, 1-4 gang