

# Product data sheet



## Smart Control 10.1''



### Reference number

SC 10

### Smart Control 10.1''

#### aspect ratio 16:9

for installation in walls, capacitive touch screen  
fanless, without rotating parts

- Door call function only in combination with Siedle Smart Gateway SG 650-..
- KNX visualisation in combination with Facility Pilot Server (ref.-no.: FAPV SERVER REG GB)
- KNX visualisation in combination with Smart Visu Server (ref.-no.: SV-SERVER-INT)
- Pre-installed iHaus-Server-App; iHaus-KNX connection exclusively via IP router (ref.-no.: IPR 200 REG) or IP interface (ref.-no.: IPS 200 REG)
- eNet visualisation in combination with eNet server for rail mounting (ref.-no.: ENET-SERVER)
- eNet visualisation in combination with eNet radio IP gateway IP (ref.-no.: FM-GATE-IP)
- Pre-installed weather page

**Update firmware prior to commissioning.**

**Please check Release Notes.**

#### Accessories:

Flush-mounted recessed box ref.-no.: SC 10 EBG

Power supply ref.-no.: NT 2415 REG VDC

#### Technical data

Screen size (W x H):	223 x 125 mm
Screen diagonal:	256 mm / 10.1''
Resolution:	WSVGA (1024 x 600), LED backlight display
Frame dimensions (W x H):	333 x 200 mm
Power consumption:	max. 15 W
Power supply:	PoE+ acc. to IEEE 802.3at, with Cat5e/Cat6 cable, length max. 100 m or DC 12 ... 32 V via external power supply (ref.-no. NT 2415 REG VDC, not included)
Operating system:	Android 4.2
Processor:	Cortex-A9
Main memory:	2 GB
Mass storage:	8 GB Flash (available disc space depends on operating system)
Slot of memory card:	microSD
Loudspeaker:	integrated
Microphone:	integrated
USB ports:	2 x USB 2.0 1 x Mini-USB OTG (accessible from the front)
LAN connections:	1 x 10/100 Mbit/s
Ambient temperature:	0 ... +30 °C

#### Version:

25.6 cm – 10.1''