


Product data sheet

Area / line coupler



Reference number

2142 REG

KNX area / line coupler

rail mounting device, 2 rail units
 ETS product family: System components
 Product type: Line coupler

- KNX Data Secure compatible with ETS 5.7.3 or higher

Function

The coupler connects two KNX data lines and ensures the electrical isolation between these lines. The definite functions of the device are defined by addressing and parameterisation.

Line coupler

Connection of a line with a main line. Alternatively with or without filter function. The coupler belongs logically to the subordinate line (here: line).

Area coupler

Connection of a main line and an area line. Alternatively with or without filter function. The coupler belongs logically to the subordinate line (here: main line).

Amplifier

Preparation and repetition of telegrams on a line, no filter function. Division of a line into max. 4 independent line segments (max. 3 line amplifiers connected in parallel per line). Each line segment requires a separate power supply including a choke.

Technical data

KNX medium:	TP 256
Power supply:	DC 21 ... 32 V from superordinate line
Current consumption	
superordinate line:	approx. 6 mA
subordinate line:	approx. 8 mA
Connection mode:	connection terminal
Mounting:	on DIN rail
Ambient temperature:	-5 ... +45 °C
Storing temperature:	-25 ... +70 °C
Protection class:	III acc. EN 61140
Mounting width:	36 mm (2 rail units)

