# merten

6.3 Conventional sensors Wind sensor with 0-10 V interface Art. no. 663591

# Wind sensor with 0-10 V interface



Colour	Article no.
polar white	663591

# **Table of Contents**

1.	Function	1	

- 2. Installation
- 3. Technical Data

#### 1. Function

The wind sensor evaluates the wind speed and converts it into an analogue 0 to 10 V output voltage. The wind sensor can be connected to the weather station REG-K/4-gang or the analogue input REG-K/4-gang. The power supply required to operate the wind sensor is made available by these devices.

# 2. Installation

The wind sensor is screwed onto e.g. a cross member or a mast with a mounting bracket (optional). A horizontal adjustment is required.



- A Cable binder
- B Cable

1

2

- © Mounting bracket
- D Cross member
- (E) Mast

The measured-value cable is fitted tightly to e.g. the cross member with clips, cable binders or similar fixing material so that the cable is not damaged at higher wind speeds by flapping and wearing through.

#### Selection of the installation site

In general, wind measuring devices should record the wind conditions in a broad radius. To obtain comparable values when determining the surface wind, measurements should be taken at a height of 10 metres above even, undisrupted ground. Undisrupted ground means: the distance between the anemometer and the obstacle should be at least ten times the height of the obstacle (see VDI 3786). If this regulation cannot be complied with, the anemometer should be installed at a height so that the measured values are influenced as little as possible by the obstacles (approx. 6 to 10 m above the obstacle).

On flat roofs, the anemometer should be placed in the middle of the roof instead of on the edge so that any preferential directions are avoided.

#### Maintenance

If the device is installed correctly, it is maintenance-free.

6.3 Conventional sensors Wind sensor with 0-10 V interface Art. no. 663591

High levels of environmental pollution can block the slit on the wind sensor between the rotating and fixed parts. This slit must always be kept clean.

# 3. Technical Data

Measuring range:	0.7 - 40 m/s, linear
Electr.output:	0 - 10 V
External supply	
Voltage:	DC 24 V (DC 18 - 32 V)
Power consumption:	approx. 12 mA
General data	
Load:	max. 60 m/s transient
Ambient temperatu-	-25 °C to +60 °C
re:	
EC guidelines:	corresponds to low voltage guideline 73/23/EEC; corre sponds to EMC guideline 89/336/EEC
Incoming cable:	3 m, LiYY 6x0.25 mm <sup>2</sup>
Fixing method:	Mounting bracket
Mounting position:	vertical

#### **Connection example:**



- $\textcircled{\begin{subarray}{c} \begin{subarray}{c} \b$
- B Cable LiYCY
- © white
- (D) brown
- (E) green
- (F) yellow
- (G) grey
- H pink
- () Shield
- J Supply 18 to 32 V DC
- K Output 0 to 10 V = 0.7 to 40 m/s

Supply for heating 24 V AC/DC
Earth