



Main

Range of product	KNX
Product or component type	Dimming actuator
Operating mode	Manual KNX bus system
Bus type	KNX

Complementary




18 mm pitches	8
Mounting support	DIN rail
[Ue] rated operational voltage	220...230 V
Network frequency	50/60 Hz
Number of outputs	4
Local signalling	LED
Load type	Incandescent lamps : 4...250 W, 230 V AC Halogen lamps : 4...250 W, 230 V AC LV halogen lamps : 25...250 VA, 12 V AC (wound transformer) LV halogen lamps : 4...250 W, 12 V AC (electronic transformer) Compact fluorescent lamp : 4...125 W, 230 V AC (RC mode) Energy saving lamp : 4...125 W, 230 V AC (RC mode) LED lamp : 4...125 W, 230 V AC (RC mode) Compact fluorescent lamp : 25...45 W, 230 V AC (RL LED mode) Energy saving lamp : 25...45 W, 230 V AC (RL LED mode) LED lamp : 25...45 W, 230 V AC (RL LED mode)

Environment

IP degree of protection	IP20
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 1521 - Schneider Electric declaration of conformity <a href="#"> Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#"> Product environmental</a>
Product end of life instructions	Available <a href="#"> End of life manual</a>