

SWITCHING ACTUATOR

paladin 683 730 rfs



Overview

- Switching actuator 1-channel for Building automation
- Functions: switching (on/off), timer, staircase lighting timer with optional advanced warning function
- Switching capacity 16A / 250V
- Additional connection for wired push-buttons
- RF-repeater function included
- Compact housing
- Flush-mounted fitting
- Protection degree IP20
- KNX-RF 1.R S-mode

Order numbers

■ paladin	
683 730 rfs	Switching actuator 1-channel Availability: approx. by the end of Q3/2018

SWITCHING ACTUATOR

paladin 683 730 rfs

Technical data

Power Supply	110-230V~ 50Hz
Switching capacity	μ 16A / 250V LED lamps 400W Incandescence / 230V Halogens 3000W Fluorescence 1300W (130μF)
KNX Medium	KNX RF 1.R
Radio Frequency	868,3 MHz
Transmission power	< 10dBm
Range	In free field: 100m Indoors: 30m
Numbers of Outputs	1
Functions	Switching actuator Timer / Staircase lighting timer with optional advanced warning function Signal repeater KNX-RF
Application Software	ETS5 or higher
Commissioning mode	System-mode (S-mode)
Dimensions	46 x 46 x 30 mm
Mounting	Flush-mounting
Operation temperature range	-10°...+45°C
Connection	screws
Degree of protection	IP20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
 Droits de modifications techniques réservés / Suscettibile di errori e modifiche

