Motion detectors sensiQ KNX

EVO white EAN 4007841 029593







Function description

King of the infrared motion detectors. The revolutionary sensIQ KNX for indoors and out, ideal for building entrances, loading bays, installation height up to 5 m, quadruple sensor system for optimum coverage over a 300° detection angle, 20 m range (tangential), metre-precision reach setting in 3 different directions. Remote control and corner wall mount bracket included. EVO white EAN 4007841 029593



Technical specifications

Туре	Motion detectors
Type of accessory	Corner adapter
Dimensions (L x W x H)	144 x 113 x 172 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	multi-storey / underground car park, outdoors, warehouse, front door, all round the building, courtyard & driveway, Indoors
Installation site	wall, ceiling, corner
Installation	Surface wiring
Switching zones	304 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Reach, radial	r = 4 m (42 m ²)

Yes
2 – 2000 lx
60 s – 255 Min.
Yes
Yes
1-255 min
Light output 2x, Presence output, Light level, Constant-lighting control, Basic light level function, Photo-cell controller, Close range, Individual pyro evaluation
Yes
ETS software, Remote control, Bus, Smart Remote
Yes
Yes
IP54
Plastic
-20 – 50 °C
white
9010
VDE
5 years
white
4007841029593

Accessories


EAN 4007841 007638 Remote control RC9

https://www.steinel.de


Motion detectors SensiQ KNX EVO white EAN 4007841 029593



Detection Zone



Dimension Drawing



Mögliche Montagehöhe: 2,00 m – 5,00 m Orange: radial Schwarz: tangential 3 skallerbare Zonen