

Motion detector

IS 3360

EAN 4007841011635



Functional description

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round radius of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m²! STEINEL Infrared technology that keeps its promises.

Technical specifications

Dimensions	65 x 95 x 95 mm
Model	Movement sensor
Sensor type	Passive infrared
Power supply	KNX bus voltage
Recommended installation height	2.5-4 m
Installation	Ceiling
Reach, tangential	20 m
Detection angle	360° with 180° angle of aperture
Twilight setting	2 - 1000 Lux
Light output	2 channels, including dimming level and basic light level
Presence output	Switching response irrespective of light level
HVAC output	Switching response irrespective of light level
Photo-cell controller output	Switching response governed by light level
Further outputs	Light level, sabotage protection
Time setting	1-255
IP rating	IP54
Temperature range	-20-+50
Version	KNX – Surface-mounted, square
Housing	UV-resistant plastic
Model	KNX

Motion detector

IS 3360

EAN 4007841011635

Sensorenerfassungsbereich 1

