IS 3360

V3 KNX - surface, rd. EAN 4007841 058180











2000w













infrared sensor 360°

m

NX max. 2000 W

2 - 1000 lux

ideal 2,5 - 4

Teach mode

manufacturer's warranty steinel-professional.de/garantie

Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

Technical specifications

Туре	Motion and Presence Detector
Dimensions (Ø x H)	126 x 65 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	outdoors, Indoors
Application, place, room	sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room
Installation site	ceiling
Type of installation	Surface wiring
Switching zones	1416 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Reach, radial	Ø 8 m (50 m²)
Reach, tangential	Ø 40 m (1257 m²)
Reach, presence	Ø 3 m (7 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	0 s – 1092 Min.
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function
With bus coupling	Yes
Settings via	Bus, ETS software, Remote control
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Manufacturer's Warranty	5 years
Version	KNX - surface, rd.
PU1, EAN	4007841058180

Motion detector

IS 3360


V3 KNX - surface, rd. EAN 4007841 058180



Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m Orange: radial Schwarz: tangential

Dimension Drawing

