

Motion detector

HF 3360

V3 KNX - concealed, sq.

EAN 4007841 058227

STEINEL
PROFESSIONAL



high frequency
sensor 360°



max. Ø 8 m



KNX



IP20



2 - 1000 lux



5 sec - 15 min



ideal 2 - 2,8 m



Teach mode



energy saving



5 JAHRE
HERSTELLER
GARANTIE
manufacturer's
warranty
steinel-professional.de/garantie

Function description

Perfection through and through. High-frequency motion detector HF 3360, ideal for basement corridors, stairwells, multi-storey car parks, installation height 2.8 m, 360° angle of coverage, reach 1 – 8 m (radial), detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls. Available either in round or square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	94 x 94 x 64 mm
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	side room, stairwell, wc, washroom, multi-storey car park, underground car park, equipment room
Installation site	wall, ceiling, corner
Type of installation	Concealed wiring
HF-system	5,8 GHz
Mounting height	2,00 – 4,00 m
Optimum mounting height	2,8 m

Sneak-by guard	Yes
Twilight setting TEACH	Yes
Time setting	0 s – 1092 Min.
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function
With bus coupling	Yes
Material	Plastic
Colour	white
Colour, RAL	9003
Version	KNX - concealed, sq.
PU1, EAN	4007841058227

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 648015	Corner wall mount 3000
EAN 4007841 035174	Corner wall mount 3000
EAN 4007841 592912	User remote control RC7 KNX

<https://www.steinel.de>

Motion detector

HF 3360

V3 KNX - concealed, sq.

EAN 4007841 058227

STEINEL[®]
PROFESSIONAL

Dimension Drawing

