

Motion detectors

IS 345 MX Highbay

V3 KNX - concealed, sq.
EAN 4007841 058302



infrared sensor
360°



max. 30 x 4 m



KNX



IP20



2 - 1000 lux



1-255 min



ideal 4 - 14 m



Teach mode



energy saving



5 JAHRE
HERSTELLER
GARANTIE
www.steinel.de/garantie
manufacturer's
warranty
steinel-professional.de/garantie

Function description

Surveillance on the highest level. Infrared motion detector IS 345 MX Highbay for indoors, ideal for large heights in depots, high-bay warehouses, machine shops, check-in areas and departure lounges, installation height 14 m, detection zone 30 x 4 m (radial), large terminal compartment for easy installation. Available as square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	94 x 94 x 78 mm
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	high-bay warehouse, Indoors
Installation site	ceiling
Installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Sneak-by guard	Yes

Capability of masking out individual segments	Yes
Reach, radial	30 x 4 m (120 m ²)
Twilight setting TEACH	Yes
Time setting	0 sec. – 1092 min
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
Material	Plastic
Colour	white
Version	KNX - concealed, sq.
PU1, EAN	4007841058302

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX


Motion detectors

IS 345 MX Highbay

V3 KNX - concealed, sq.
EAN 4007841 058302

STEINEL[®]
PROFESSIONAL

Detection Zone



Mögliche Montagehöhe: 4,00 m – 14,00 m
Orange: radial und tangential

Dimension Drawing

