

Photo-cell controller

Light Sensor Dual

V3 KNX - concealed, rd.
EAN 4007841 058340

STEINEL[®]
PROFESSIONAL



Twilight switch +
eco-mode



KNX



IP20



2 - 1000 lux



max 4 m



CE



5 JAHRE
HERSTELLER
GARANTIE
steinel-professional.de/garantie

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

| | | | |
|--------------------------|---|----------------------------|--|
| Type | Constant-lighting controller | Basic light level function | Yes |
| Dimensions (Ø x H) | 124 x 51 mm | KNX functions | Light output 2x, Light level, Constant-lighting control, Photo-cell controller |
| Sensor Technology | Light sensor | With bus coupling | Yes |
| Application, place | Outdoors, Indoors | Settings via | ETS software, Remote control, Bus, Smart Remote |
| Application, place, room | classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room, Indoors | IP-rating | IP54 |
| Installation site | wall, ceiling | Version | KNX - concealed, rd. |
| Installation | Concealed wiring | PU1, EAN | 4007841058340 |
| Mounting height | 2,00 – 4,00 m | | |

Accessories

| | |
|--------------------|--------------------------------|
| EAN 4007841 009151 | Remote control Smart Remote |
| EAN 4007841 593018 | Service remote control RC6 KNX |
| EAN 4007841 592912 | User remote control RC7 KNX |

Photo-cell controller

Light Sensor Dual

V3 KNX - concealed, rd.

EAN 4007841 058340

STEINEL[®]
PROFESSIONAL

Dimension Drawing

