

Presence detector

IR Quattro HD

V3 KNX

EAN 4007841 058470

STEINEL[®]
PROFESSIONAL



infrared sensor



max. 8m x 8m
presence

HD

4800 zones

KNX[®]

KNX 4 channel



ideal 2,5 - 10 m



indoor sensor

iQ

iQ-mode



energy saving

5 JAHRE
HERSTELLER
GARANTIE

manufacturer's
warranty
steinel-professional.de/garantie

CE

CE

Function description

Detection no finer! Infrared presence detector Presence Control PRO IR Quattro HD KNX for indoors, ideal for medium to large-size offices, conference and meeting rooms, classrooms and lecture theatres, sports halls and warehouses, installation height up to 10 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 4800 switching zones for the ultimate in detection quality, presence detection over a true 64 m², square detection zone, mechanically scalable.

Presence detector

IR Quattro HD

V3 KNX

EAN 4007841 058470



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	50 x 120 x 120 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	Open-plan office, high-bay warehouse, conference room, sports hall, classroom
Installation site	ceiling
Type of installation	Concealed wiring
Switching zones	4800 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,50 – 10,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	360 °
Sneak-by guard	No
Capability of masking out individual segments	No
Reach, radial	8 x 8 m (64 m ²)
Reach, tangential	20 x 20 m (400 m ²)
Reach, presence	8 x 8 m (64 m ²)

Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Basic light level function in per cent	10 – 50 %
Basic light level function time	Permanently ON, 1-255 min, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Ambient temperature	-25 – 55 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX
PU1, EAN	4007841058470

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Presence detector

IR Quattro HD

V3 KNX

EAN 4007841 058470

STEINEL[®]
PROFESSIONAL

Dimension Drawing

