

Presence detector

IR Quattro SLIM KNX

V3 KNX

EAN 4007841 058494

STEINEL[®]
PROFESSIONAL



infrared sensor
max. 4m x 4m
presence



max. 4 x 4 m
presence



KNX 4 channel



10 - 1000 lux with
RC 6



1 min - 15 min with
RC 6



ideal 2,5 - 4 m



indoor sensor

TEACH

Teach mode with
RC 6

iQ

iQ-mode

5 JAHRE
HERSTELLER
GARANTIE

manufacturer's
warranty
[steinel-professional.de/garantie](https://www.steinel.de/garantie)

Function description

Genuine 16 m² of presence detection concentrated on 4 mm. Control PRO IR Quattro SLIM KNX presence detector for indoors, ideal for small offices, store, service and utility rooms, washrooms and WCs, for mounting at a height of up to 4 m, with digital BUS interface for controlling 4 lighting channels and HVAC.

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	77 x 77 x 55 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	one-person office, hotel room, care room, function room / ancillary room, WC / washroom, Indoors
Installation site	ceiling
Installation	Installation
Switching zones	260 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	71 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	8 x 8 m (64 m ²)

Reach, presence	32 x 32 m (1024 m ²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 min
Constant-lighting control	No
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Interconnection	Yes
IP-rating	IP20
Material	Plastic
Ambient temperature	0 – 40 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX
PU1, EAN	4007841058494

<https://www.steinel.de>

Presence detector

IR Quattro SLIM KNX

V3 KNX


EAN 4007841 058494

STEINEL[®]
PROFESSIONAL

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m
Orange: Präsenz, tangential und radial

Dimension Drawing

