

# KNX ENO 634 (32-Kanal AP)

## Bidirectional Gateway between EnOcean and KNX Bus

Data sheet

### Application

The unit KNX ENO 634 serves as a bidirectional gateway between EnOcean radio devices and the KNX-bus. With this device, commands and measured values of EnOcean wireless sensors can be transferred to the KNX-bus, for example, to control KNX actuators. Also EnOcean wireless actuators can be controlled via KNX.



Fig.: KNX ENO 634

In addition the gateway supports logical and control functions and has a radio repeater included. The KNX ENO 634 is organized in 32 channels. Each channel can be assigned to one of the following functions:

- Link to sensors:
  - Push buttons (switching, dimming, shutter, scene)
  - Window contacts and handles
  - Access card and other switches
  - Temperature, humidity and light sensors
  - Presence sensors
  - Gas and environmental sensors (weather station)
  - Room control devices
  - Automated counter devices
  - Digital inputs
- Link to actuators:
  - Switch
  - Dimmer
  - Shutter
  - HVAC actuators (valves)
- Time control / logic:
  - Switch-on delay
  - Switch-off delay
  - Gates (e.g. AND, OR, XOR)
  - Flip-flop (Toggle)
- Regulation / room control
  - Two point controller
  - Continuous regulator
  - Heat requisition
  - Lighting control
- Special (Trigger, Valuator, Watchdog)

The configuration of the device and the channels is done using the ETS software via the KNX bus. For the teach-in of the wireless components the keys and the display in the device are used.

### Technical Specification

#### Electrical safety

- Protection class (EN 60529): IP 20
- Safety extra low voltage SELV 29 VDC

#### CE marking according to

- Low voltage directive 2014 / 35 / EU
- EMC directive 2014 / 30 / EU
- Radio equipment directive 2014 / 53 / EU
- RoHS directive 2011 / 65 / EU (RoHS2)  
EN 50491-3: 2009, EN 50491-5-1: 2010  
EN 50491-5-2: 2010, EN 50491-5-3: 2010  
EN 61000-6-2: 2005,  
EN 61000-6-3: 2007 + A1: 2011  
EN 300 220-2: V3.1.1  
EN 50581: 2012 (RoHS2)

\*CE declaration can be requested at [info@weinzierl.de](mailto:info@weinzierl.de).

#### Environmental requirements

- Ambient operating temp.: 0 ... + 45 °C
- Storage temp.: - 25 ... + 70 °C
- Rel. humidity (not condens.): 5 % ... 93 %

#### Mechanical data

- Housing: plastic, white
- Surface mounting, matches on 55 mm flush-mounted box
- Dimensions: 81 x 81 x 25 mm
- Weight: approx. 90 g

#### Power supply

- Powered via bus  
Current consumption: approx. 12 mA

#### Connections

- KNX connection via terminal block

#### RF Interface

- EnOcean, ISM Band 868.3 MHz, ASK
- Output power: 3dBm
- Distance: see [www.enocean.com](http://www.enocean.com)

#### Supported EnOcean devices

- According to EnOcean Profiles EEP Version 2.1
- See operating and installation instructions



**Weinzierl Engineering GmbH**

D-84508 Burgkirchen / Alz  
Germany

<http://www.weinzierl.de>  
[info@weinzierl.de](mailto:info@weinzierl.de)