Motion detector - Professional Line

HF 3360

V3 KNX - surface, rd. EAN 4007841 058234 Article number 058234























5 years

manufacturer's warranty steinel-professional.de/garantie

Function description

Perfection through and through. High-frequency motion detector HF 3360, ideal for basement corridors, stairwells, multi-storey car parks, installation height 2.8 m, 360° angle of coverage, reach 1 – 8 m (radial), detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls. Available either in round or square surface-mounted and concealed version.

Motion detector - Professional Line

HF 3360

V3 KNX - surface, rd. EAN 4007841 058234 Article number 058234



Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	126 x 52 mm
Power supply, detail	KNX bus
Sensor Technology	High frequency
Application, place	Indoors
Installation site	wall, ceiling, corner
Installation	Surface wiring
Mounting height	2,00 – 4,00 m
Reach, radial	Ø 8 m (50 m²)
Reach, tangential	Ø 8 m (50 m²)
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	180 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	Yes

Time setting 5 s - 15 Min. Constant-lighting control Yes Basic light level function Yes Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate With bus coupling Yes Settings via ETS software, Remote control, Bus, Smart Remote With remote control No Interconnection Yes Type of interconnection Master/slave IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd. PU1, EAN 4007841058234	Twilight setting	2 – 1000 lx
Basic light level function Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate With bus coupling Yes Settings via ETS software, Remote control, Bus, Smart Remote With remote control No Interconnection Yes Type of interconnection IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour Colour, RAL 9003 Manufacturer's Warranty Version KNX - surface, rd.	Time setting	5 s – 15 Min.
Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate With bus coupling Yes Settings via ETS software, Remote control, Bus, Smart Remote With remote control No Interconnection Yes Type of interconnection IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour Colour, RAL Manufacturer's Warranty Version White Constant-light level, HVAC output, Constant-lighting control, Light output, Day / night level, FVAC function, Light level, HVAC output, Constant-lighting control, Light output, Day / night function, Basic light level function, Light output, Day / night function, Basic light level function, Light output, Day / night function, Light function, Light output, Day /	Constant-lighting control	Yes
KNX functions function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate With bus coupling Yes Settings via ETS software, Remote control, Bus, Smart Remote With remote control No Interconnection Yes Type of interconnection IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour White Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Basic light level function	Yes
Settings via ETS software, Remote control, Bus, Smart Remote With remote control No Interconnection Type of interconnection IP-rating IP54 Material Plastic Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour Colour, RAL Manufacturer's Warranty Version ETS software, Remote control, Bus, Smart Remote No No Master/slave IP54 Material Plastic -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors KNX - surface, rd.	KNX functions	Constant-lighting control, Light output 2x, Presence output, Day /
Settings via Smart Remote With remote control No Interconnection Yes Type of interconnection IP-rating IP54 Material Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour Colour, RAL 9003 Manufacturer's Warranty Version Moster/Slave IP54 Master/slave IP54 Flastic Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors KNX - surface, rd.	With bus coupling	Yes
Interconnection Yes Type of interconnection Master/slave IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Settings via	
Type of interconnection Master/slave IP-rating IP54 Material Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour Colour, RAL 9003 Manufacturer's Warranty Version Master/slave Flave Flave Function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors KNX - surface, rd.	With remote control	No
IP-rating IP54 Material Plastic Ambient temperature -20 - 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Interconnection	Yes
Material Plastic Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Type of interconnection	Master/slave
Ambient temperature -20 – 50 °C function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	IP-rating	IP54
Application, room function room / ancillary room, stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Material	Plastic
Application, room stairwell, WC / washroom, multi-storey / underground car park, Indoors Colour white Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Ambient temperature	-20 – 50 °C
Colour, RAL 9003 Manufacturer's Warranty 5 years Version KNX - surface, rd.	Application, room	stairwell, WC / washroom, multi-storey / underground car park,
Manufacturer's Warranty 5 years Version KNX - surface, rd.	Colour	white
Version KNX - surface, rd.	Colour, RAL	9003
1417 Carracoj a	Manufacturer's Warranty	5 years
PU1, EAN 4007841058234	Version	KNX - surface, rd.
	PU1, EAN	4007841058234

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 056698	Black cover for HF 3360


Motion detector - Professional Line

HF 3360

V3 KNX - surface, rd. EAN 4007841 058234 Article number 058234



Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m Orange: radial und tangential

Dimension Drawing

